
.129 HOLE
1/8 x 5/16 2S-O ALUM. BR. HD. RIVETS
12 REQ'D.
CLIP
COWL
SECTION A-A
FULL SIZE
22471
SECTION B-B
TYPICAL LOCK SEAM
FULL SIZE
SECTION C-C
FULL SIZE
.129 HOLE
1/8 x 5/16 2S-O ALUM. BR. HD. RIVETS
SPACED APPROX. 2 IN. APART
42 REQ'D.
.098 HOLE IN COWL
3/32 x 1/4 2S O ALUM. BR. HD. RIVETS
26 REQ'D.
COLLAR
3
COWL
11/16
FIREWALL
SECTION D-D
TYPICAL ATTACHMENT
FULL SIZE
6054 / D6079-A (USED ON ASS'Y A661 ONLY)
6038 / D6079-C (USED ON ASS'Y A661 ONLY)
.098 HOLE
3/32 x 1/4 2S-O ALUM. BR HD. RIVETS
SPACED APPROX. 2 IN. APART
16 REQ'D.
.093 HOLE
#6 TYPE 'A' P.K. SCR.
2 REQ'D.
E
E
4 7/8
6
7
1/8
7 1/4
3
1/4
COWL BODY
FRONT EDGE OF COWL
FIG. I
23432
D
D
6145 / D6074-C (USED ON ASS'Y A6031 ONLY)
6149 / D6074-C (USED ON ASS'Y A661 ONLY)
6055 / D6075-C
B
B
C
C
41 IN. TO SEAM
DIMENSION TAKEN
ALONG EDGE OF COWL
SEE FIG. I FOR INSPECTION PLATE INSTALLATION
ATTACHMENT STRIP
PLATE
COWL BODY
1/4
SECTION E-E
FULL SIZE

ASS'Y. PART NO. A6031 (WITHOUT INSPECTION PLATE)
ASS'Y. PART NO. A661 (WITH INSPECTION PLATE)

APR 21 1972

LIMITS, SHOP PRACTICES AND FINISH, UNLESS OTHERWISE NOTED TO BE IN ACCORDANCE WITH PIPER SPECIFICATIONS 89 AND 810.

NOTE: DESIGN INFORMATION TAKEN FROM PART SUPPLIED BY SERVICE DEPARTMENT.

LET.	REVISION	DATE	SR.	BY
A	NOTE ADDED	12-13-47		J.E.V.

MODEL	PER SHIP	NEXT ASSEMBLY	SUPERSEDES	SUPERSEDED BY
J5	1			

PART No.	No. REQ.	MATERIAL

SCALE 2 IN. = 1 FT. & NOTED

COWL ASS'Y - FUSELAGE

PIPER AIRCRAFT CORP.
LOCK HAVEN, PENNA.

DRAWN	CHECKED	APPROVED
R. REEDER 5-3-44	R.E.T. 5-10-44	

D6078-C